

RUBBER BASED - NON CURING


Non-Curing rubber based Butyl mastic putty & tapes are highly tacky compounds possessing excellent peel strength & good adhesion to metal & non-metal with good weathering properties.

SALIENT FEATURES :

- High elongation.
- Posses excellent peel strength.
- Highly tacky compound.
- Effectively seals and dampens vibration.
- Excellent addition on most of the substrates

APPLICATIONS :

- Sealing on airconditioner compressor and condensor to prevent entry of water and moisture.
- Insulating compounds in bus bar joints, electrical connections.
- Door trim sealing for preventing ingress of moisture and vibration.
- Sound dampening pads for noise reduction in Automobiles, Air conditioners and gensets.
- Sealing joints encountered in pre-engineered metal building fabrication such as vents, gutters, roof jacks, window tins, door fins etc



TECHNICAL SPECIFICATION - NON - CURING RUBBER

| Grade | Colour / Appearance | Dimension | Specific Gravity @ (27°C-33°C) | Volatile Content % | Penetration | Packing | |
|---------------------------|------------------------------------|-------------------------------------|---|---|-------------------------|--|--|
| BUTYL MASTIC PUTTY | Anaplast R | Yellow,Blue,Red & Black/Roll form | 35mm x 2mm x 1mtr | NA | NA | 70 - 110 (27°C - 30°C) 100gm weight | Rolls as per customer dimension |
| | A - 832 | Light Grey / Putty | NA | 1.7 - 1.9 | 80°C for 72hrs ≤ 0.30 % | 110 - 150 (30°C) 50gm weight | 1kg & Lumpsum as per customer dimension |
| BUTYL TAPES | Stik-on (Reusable Adhesive) | Greyish White | 45mm (W) x 3mm (T) x 25mm (L) | 1.3 - 1.5 | ≥ 99 (105±2°C/ 3 hrs) | 45 - 65 30 ± 2°C 50gm weight | 10gm,50gm&Strips as per customer requirement |
| | A - Door Foil Adhesive | Black / Smooth Bead | 6mm (W) x 2.5mm (T) x 5mtrs (L) | 1.10 - 1.20 | Non Volatile Content | @ (26 - 29°C) 45 - 60 | Rolls as per customer dimension |
| | A - 846 HT | Yellow / Smooth Bead | 12.5mm (W) x 3.2 mm (T) x 7.5mtrs (L) | 1.00 - 1.40 | ≥ 99 (105±2°C/ 3 hrs) | @30°C 50gm weigh 50 - 70 | Rolls as per customer dimension |
| | A - 891 (Cork Filled) | Black / Tape form | 50mm (W) x 3 mm (T) x 30ft (L) | 1.30 - 1.40 | NA | NA | Rolls as per customer dimension |
| | A - 899 | Black, Grey & Off-White / Tape Form | 5mm (T) x 6 mm (W) x 9.5mtrs (L) 2.2mm x 10.2mm x 10mtrs 2.4mm x 9.5mm x 15.3mtrs | Black & Off White Spec 1.40 - 1.50 Grey Spec 1.3 - 1.5 | NA | 50 - 70 85 - 110 @27 - 33 | Rolls as per customer dimension |